

Appl. No. 10/799,175
Response to Office Action mailed April 25, 2005

Att'y Dkt. No. 114208-023

LISTING OF CLAIMS

This listing of claims replaces all prior versions and listings of claims in the patent application.

Claim 1 (currently amended): A slide fastener with a separable bottom end stop in which fastener elements are attached to opposing sides edges of a pair of fastener tapes, comprising a separable bottom end stop made of synthetic resin which is attached to the opposing side edges of the fastener tapes at end portions of the fastener elements, and a reinforcement portion which is formed integrally with the separable bottom end stop and extended toward at least one surface of the fastener tapes, wherein the reinforcement portion ~~is formed of~~ comprises an inside portion formed of plural ribs disposed obliquely as seen in its plan view view, which are provided in an inside portion on a side connected to the separable bottom end stop and an outside portion connected to the inside portion and extended toward an outer edge of one of the fastener tapes, the outside portion being formed of plural ribs disposed in parallel with a predetermined interval.

Claim 2 (currently amended): The slide fastener with the separable bottom end stop according to claim 1, wherein the reinforcement portion is so configured that the ribs are disposed symmetrically on both surfaces of the fastener tape while the inside portion ~~is~~ is formed thinner than an outside portion.

Claim 3 (original): The slide fastener with the separable bottom end stop according to claim 1, wherein an intersecting portion of the ribs is formed in an arc-like configuration as seen in its plain view.

Claim 4 (original): The slide fastener with the separable bottom end stop according to claim 1, wherein a concave portion is formed among the ribs in the inside portion of the reinforcement portion.

Claim 5 (original): The slide fastener with the separable bottom end stop according to claim 1, wherein a cut-out which is dented toward a top end is formed in a bottom edge of the

Appl. No. 10/799,175
Response to Office Action mailed April 25, 2005

Am. Dkt. No. 114208-023

inside portion of the reinforcement portion.

Claim 6 (cancelled)

Claim 7 (currently amended): The slide fastener with the separable bottom end stop according to ~~claim 6~~ claim 1 having a rib for connecting front ends of the plural ribs wherein the rib has a parallel ~~portion~~ portion that is parallel to an outside edge portion extending in a parallel direction with the length direction of the fastener tape at a bottom end side of the reinforcement portion and a bent portion bending in a direction parting from an outside edge portion of the fastener tape at an upper end side of the reinforcement portion.

Claim 8 (currently amended): The slide fastener with the separable bottom end stop according to claim 1, wherein bottom ends of the inside portion and an outside portion of the reinforcement portion are formed farther from a bottom end of the fastener ~~tape~~ tape than a bottom end of a box pin or an insert pin are is.

Claim 9 (currently amended): The slide fastener with the separable bottom end stop according to ~~claim 7~~ claim 8, wherein the bottom end of the box pin or the insert pin is disposed adjacent to the bottom end of the fastener tape and an adhered portion in which yarns composing the fastener tape adhere each other is formed at the bottom end of the fastener tape.

Claim 10 (currently amended): The slide fastener with the separable bottom end stop according to claim 1, wherein a side edge portion of each of the fastener tapes opposing an outer end portion of the reinforcement portion opposite to the a box of a separable bottom end stop is formed into a rough structure and the outer end portion of the reinforcement portion penetrates into the rough structure.

Claim 11 (original): The slide fastener with the separable bottom end stop according to claim 1, wherein, in the inside portion of the reinforcement portion, width from an inside end faces of the fastener elements toward an inside of each of the fastener tapes is within 4.0 mm.